

Seriya JIVA KS-7700

www.posiflex.com

POSIFLEX
Your Success is Our Vision



| Specification | JIVA KS-7715 | JIVA KS-7717 |
|-----------------------------|---|--|
| Processor | Intel Core i3 2.2 GHz / 3 M cache CPU Intel Core i5 2.5 GHz / 3 M cache CPU | |
| System Memory | DDR3 1066 MHz, SO-DIMM socket x 2, max 16 GB, default 4 GB | |
| Storage Device | 2.5" SATA HDD x 2 or SSD Kit (Optional) | |
| Power Supply | 12V DC power adaptor, 120W (Optional 150W when equipping with 2nd 15" LCD LM-8015 / 8025 / 8035 / 8045 / 8055 / TM-8045, Black Only) | |
| Audio | 2W speaker x 2, line out | |
| OS support | Win 7 / Windows XP Pro / POSReady 7 / POSReady 2009 | |
| Color | Black / White | |
| Display | | |
| LCD | 15" TFT LCD, 1024 x 768 resolution | 17" TFT LCD, 1280 x 1024 resolution |
| Touch Function | Resistive, 5-wire, USB Interface / IR touch, USB Interface Bezel-free, Resistive touch, USB Interface Bezel-free, PC touch, USB Interface | Resistive, 5-wire, USB Interface / IR touch, USB Interface |
| Brightness Control | By push button | |
| Tilt Adjustment | From 15° to 70° | |
| Connectivity | | |
| LAN Port | 10 / 100 / 1000 Mb | |
| Parallel Port | Optional | |
| Serial Port | DB9 x 3, RJ-45 x 1 (Optional RJ45 to DB9 cable) with 5V / 12V support on COM1 / COM2 / COM3 / COM4 | |
| UPS Port | Yes, battery (Optional) | |
| Standard USB Port | 7 (6 on the I/O plate, 1 on the left side) | |
| Proprietary USB Port | 1 for side mount options | |
| Powered USB | 1 X 24V via 5.5th gen base (Upgrade to 150W power adaptor when equipped with Powered USB) | |
| VGA Port | D-SUB 15 pins, with 12V power for Posiflex LCD monitor | |
| CR Port | 1, control 2 CR | |
| Physical Dimension | | |
| Dimension (W x D x H in mm) | 378 x 312 x 340 | 410 x 312 x 385 |
| Weight (N. W. in kg) | 9.25 | 11.7 |
| Environment | | |
| Operation Condition | 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD) | |
| Storage Condition | (-20°C) - 70°C, 10%RH - 90%RH | |
| Options | | |
| SSD | 8 GB minimum | |
| 2nd HDD | 2.5" SATA HDD | |
| RAID Function | Support RAID 1 (Disk mirroring) | |
| UPS Battery | 2300 mAh/12V | |
| WiFi | 802.11 b / g / n, USB interface | |
| 2nd LCD Display | 15" LM-8015 / 8025 / 8035 / 8045 / 8055 / TM-8045, 12" LM-6101B/LM-2312, 10" LM-2310 (Black Only) | |
| MSR | See security device | |
| Security Device (SD) | SD-466/SD-466Z : 3 tracks MSR (Optional JIS-II) and/or fingerprint sensor (Black / White) SD-666W : 3 tracks MSR (Optional JIS-II) and/or iButton (Black Only) SD-866W : 3 tracks MSR (Optional JIS-II) and/or RFID and/or WiFi (Black / White) | |
| PD-306 / PD-306U | 2 x 20 LCD, default 200 mm pole (Black Only) | |
| PD-309 / PD-309U | 2 x 20 LCD, default 200 mm pole (Black Only) | |
| PD-310 / PD-310U | 2 x 20 LCD, rear top mount (Black / White) | |
| PD-2602 / PD-2602U | 2 x 20 VFD, default 200 mm pole (Black Only) | |
| PD-2604 / PD-2604U | 2 x 20 VFD, rear top mount (Black / White) | |
| PD-2605 / PD-2605U | 2 x 20 VFD, default 200 mm pole (Black Only) | |
| PD-76X2 | 240 x 64 dot graphics LCD, 200 mm pole (Black Only) | |
| KP-300W | 36 Key plus lock keypad and/or MSR and/or smart card reader (Black Only) | |
| Certifications | | |

Seriya JIVA KS-7700

Prvi fanfree POS sustav na svijetu koji koristi *Intel Core i5*
Elegantan dizajn bez okvira



Design and Manufacturing In Taiwan by Posiflex Technology Inc.

2013 KS77Q4C1

** Only 1.5V DDR3 memory is supported.

** The product information and specifications are subject to change without prior notice.

POSIFLEX Posiflex Technology, Inc.
Headquarters
No.6, Wuquan Rd., Wugu Dist., New Taipei City
248, Taiwan (R.O.C.)
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

www.posiflex.com

Seriya JIVA KS-7700

Posiflex predstavlja prvi *fanfree* POS sustav na svijetu koji koristi *Intel Core i5*, seriju JIVA KS 7700. Serija JIVA KS-7700 može maksimalno koristiti CPU *Intel Core i5*, sigurnosnu kopiju RAID i UPS, a sadrži zaslon osjetljiv na dodir bez okvira u moderniziranom i patentiranom kućištu od lijevanog aluminija. Otmjen izgled popraćen dizajnom bez okvira i tankim postoljem čini uređaj elegantnim. Ugrađeni UPS nalazi se u matičnoj ploči koju je razvio Posiflex kao pričuvni izvor energije. *Fanfree* dizajn donosi pak zaštitu od prašine i tih rad, što omogućuje s jedne strane rad u teškim uvjetima, a s druge strane rad u tihom okruženju. Osim toga, serija JIVA KS-7700 podržava raznovrsne dodatke i periferne uređaje poput bežičnog modula, čitača magnetskih kartica, zaslona za kupca i programabilne tipkovnice te širok raspon povezivosti koji omogućuje brojne oblike primjene.

Seriya JIVA KS-7700 nastoji zadovoljiti potrebe trgovina na malo više kvalitete.



s drugim LCD zaslonom

s čitačem bar koda

sa zaslonom za kupca

s čitačem magnetskih kartica i s čitačem otisaka prstiju

podesiv zaslon



patentirano kućište od lijevanog aluminija

zaslon osjetljiv na dodir: otporni, infracrveni, otporni bez okvira ili bez okvira (zaslon bez okvira opcija je samo za seriju JIVA KS-7715)

Ključne značajke

- ▶ koristi maksimalno *Intel Core i5* 2,5 GHz (opcija) i memoriju DDR3
- ▶ zaslon osjetljiv na dodir: otporni, infracrveni, otporni bez okvira ili bez okvira (zaslon bez okvira opcija je samo za seriju JIVA KS-7715)
- ▶ 17-inčni LCD ekran rezolucije 1280 x 1024 (JIVA KS-7717) ili 15-inčni LCD ekran rezolucije 1024 x 768 (JIVA KS-7715)
- ▶ RAID 1 (zrcaljenje diska) kao sigurnosna kopija za važne podatke
- ▶ UPS (ugrađen u matičnu ploču koju je razvio Posiflex) kako bi se izbjegao iznenadan nestanak napajanja tijekom transakcije
- ▶ *fanfree* dizajn za tih rad i protiv prašine
- ▶ patentirano kućište od lijevanog aluminija za učinkovito hlađenje
- ▶ poklopac koji štiti prekidač od slučajnog gašenja
- ▶ prolaz za kabel na dnu kućišta i poklopac radi sigurnosti i urednosti
- ▶ čvrsto i tanko postolje
- ▶ sjajan crni ili bijeli prednji okvir (opcija).