



TX-4200 TX-4200E

Univerzalan uređaj

Seriya TX-4200 univerzalan je uređaj idealan za različite oblike primjene. Zahvaljujući svojem kompaktnom kućištu, CPU-u *Intel Cedarview Dual Core*, standardnom priključku za zaslon VGA + HDMI, mini utoru za proširenje PCIe za WiFi, priključku PS/2, postolju VESA i drugim mogućnostima, seriya TX-4200 toliko je svestrana da se može koristiti kao pravi POS box, kao kontroler za kuhinjski sustav za video nadzor, kao kontroler za digitalni potpis ili u bilo kakvoj industrijskoj primjeni.

- kompaktnost radi različitih oblika primjene
- priključak za zaslon HDMI idealan za primjenu digitalnog potpisa
- unutarnji WiFi putem mini utora za proširenje (nije dostupno kod TX-4200; opcija kod TX-4200E)
- postolje VESA radi fleksibilnosti pri postavljanju
- USB priključak 24 V (nije dostupno kod TX-4200; opcija kod TX-4200E).

TX-4200 TX-4200E



• POS



• Digital Signage



• KVS

Specification	TX-4200	TX-4200E
Processor	Intel Cedarview dual core D2550 CPU, 1.86GHz, 1M Cache	Intel Cedarview dual core D2550 CPU, 1.86GHz, 1M Cache
System Memory	DDR3 1066MHz, SO-DIMM x 1, max. 4GB	DDR3 1066MHz, SO-DIMM x 1, max. 4GB
Storage Device	2.5" SATA HDD or SSD; factory default 320GB HDD	2.5" SATA HDD or SSD; factory default 320GB HDD
Power Supply	12V DC power adaptor, 60W	12V DC power adaptor, 80W (150W with 2nd VGA and/or Powered USB option)
Audio	Line-out and 2W internal speaker	Line-out
OS Support	Windows 7 32bit / POSReady 7 32bit / Windows XP Pro / POSReady 2009	Windows 7 32bit / POSReady 7 32bit / Windows XP Pro / POSReady 2009 / Linux
Connectivity		
LAN Port	10 / 100 / 1000Mb	10 / 100 / 1000Mb
Serial Port	DB9 x 2 + RJ45 x 2 with 5V/12V support on COM1 / COM2 / COM3 / COM4, RJ-45 to DB9 cable optional	DB9 x 2 + RJ45 x 2 with 5V/12V support on COM1 / COM2 / COM3 / COM4, RJ-45 to DB9 cable optional
UPS Port	N/A	N/A
Standard USB Port	6	6
PS/2 Port	Yes	Yes
VGA Port	D-SUB, 15 pins, with 12V support for Posiflex monitor	D-SUB, 15 pins, with 12V support for Posiflex monitor
HDMI Port	Yes	Yes
Mini-PCIe slot	N/A	Yes
CR Port	1, control 2 CR	1, control 2 CR
Physical Dimension		
Dimension (W x D x H in mm)	220 x 202 x 56	220 x 202 x 56
Weight (N.W. in Kg)	1.29	1.31
Environment		
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH	(-20°C) - 70°C, 10%RH - 90%RH
Options		
SSD	8GB minimum	8GB minimum
COM5 + COM6	N/A	DB9, with 5V/12V support
2nd VGA Port	N/A	Yes, with 12V support
Powered USB Port	N/A	1 x 24V
WB-4200 wall mount bracket	Yes	Yes
WIFI	External USB dongle	Mini-PCIe WIFI module
Certifications		

Design and Manufacturing In Taiwan by Posiflex Technology Inc.

The product information and specifications are subject to change without prior notice.

Intel does not offer Cedarview platform HDMI support under Windows XP Pro / POSReady 2009 environment.

2013Q3C1



Posiflex Technology Inc. (Headquarters)

TEL +886-2-2299-1599 FAX +886-2-2299-1819

MAIL sales@posiflex.com.tw WEB www.posiflex.com

No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan

Authorized Distributor / Reseller